

Efficient Light

Built to last.



MINESPEC LED 168K-9

ECONOMIC LIGHT

50,000 hours of
life for every light.

BUILT TOUGH

Built to the highest
standards.

SUPER SAFE

Designed with
the latest safety
innovations.



Construction
& Civil



Mining &
Quarries



Rental



Industrial




Agriculture



WE KNOW WHERE WE STAND

- No loss of light output after stabilisation
- Each LED flood light provides 28,000 effective lumens after stabilisation (IES standard - LM 79-08). Photometric Light Plots based on NATA approved testing parameters confidently state that the light output will match field testing
- Perkins 2cyl water-cooled engine
- Extra low voltage (DC). OH&S risk elimination
- Stabilised power consumption of the LED is 300W nominal
- 6 x 300W low-glare, RFCOMSafe lamps producing 168,000 lumens
- Refuel every 4 weeks – on basis of 12 hour operation each night
- 18t annual carbon footprint reduction per tower compared with metal halide equivalent
- SmartGen system with start/stop and performance monitoring (optional)
- Complete plug and play system with no hard wired componentry makes for easy part and loom servicing or replacement
- 50,000 hours of life per light
- 500-hour service intervals
- Light instant-on (no warm-up/cool down)
- Built in Australia



Height	2.49m (8' 2")
Length	4.71m (15' 5")
Width	2.08m (6' 10")
Weight (Wet)	1,630kg (3,594lb)
Fuel	Diesel
Fuel Capacity	300L (79 US Gallons)
Fuel Tank	LLPDE
Fuel Consumption	0.85 L/hr (0.22 US Gallons)
Engine	Perkins 402D-05
No. Engine Cylinders	2
Engine Aspiration	Naturally aspirated
Alternator	FB4-48/100
Power Generation	Extra low voltage (DC)
Electrical System	48V DC
No. Lights	6
Type of Lights	300W LED
Total Light Output	168,000 lumens
Light Tilt	Hydraulic
Mast Rotation	144° manual
Mast Raise/Extension	9m (29' 6") hydraulic
Trailer	Single axle
Tire and Rim Size	205 R16
Stabiliser Supports	4 x wind down
Tow Hitch	50mm ball (1.9") 2000kg (4409lb)
Also Includes	2 Pole Bosch battery isolator with locksafte actuator (Red) 1 Pole starter motor isolator (Yellow) Anderson jump start receptacle Emergency stop button Timer start/stop functions

OPTIONS

- Hydraulic light bar rotation
- Hydraulic post rotation
- Hydraulic stabiliser legs
- CAT jumpstart
- Wiggins Fast Fill
- Additional 90L fuel tank
- Wheel chocks
- Heavy duty drag skid
- Twin axle trailer
- Coal mining wiring specs
- Fire extinguisher
- Remote comms
- GPS location

LAMPS
POWERED
BY HELLA



Final weight and dimensions will depend on completed specifications and options, subject to manufacturing tolerances. All the information in this document is substantially correct at the time of creation and may be altered at the manufacturer's sole discretion. Any quotes and related material provided supersedes the contents hereof.