

NOW UP TO
29%
MORE
LIGHT

EFFECTIVE LIGHT

ALLIGHT
MSGEN3 
SMARTER. BRIGHTER. TOUGHER.

MINESPEC GEN3 HYDRAULIC

ECONOMIC LIGHT

50,000 hours of
life for every light.

BUILT TOUGH

Built to the highest
standards.

SUPER SAFE

Designed with safety
at its core.

NOW WITH ALLUME 190

LED TECHNOLOGY

85.5K lm/light | 190 lm/W

UP TO 29% MORE LIGHT



Construction
& Civil



Mining &
Quarries



Rental



Industrial



Agriculture

ALLIGHT

MINESPEC GEN3 HYDRAULIC

Allight's MineSpec lighting tower with hydraulic stabilisers is designed for the harshest conditions, with each LED floodlight delivering 85,500 effective lumens after stabilisation.

Built in Western Australia. Proven worldwide. The Allight MineSpec Gen3 Hydraulic delivers reliable performance in the toughest mining environments. Invest in equipment you can trust. Invest in Allight.

LIGHTS

Type	Allight LED Third party certified to IES LM79-19
Total output (lm)	342,000
Number of lights	4
Lights power (W)	450
Lights efficacy (lm/W)	190
Lifetime (h)	50,000

MAST

Height (m)	9
Mast extension	Hydraulic
Mast manual rotation (°)	144
Light bar tilt (°)	94
Light bar rotation (°)	355
Light bar tilt and rotation	Hydraulic

ENGINE

Type	Perkins 402-05D naturally aspirated
Speed (rpm)	1800
Fuel consumption (l/hr)	0.85
Running time - per tank (h)	353
Service requirements (hr)	500
Fuel tank size (l)	300
Fuel tank type	LLDPE
Filter	Spin on fuel filter, Perkins dual air filter
Noise levels dB(A)@7m	65

ALTERNATOR / GENERATOR

Type	Sincro FB4-48/100
Voltage (VDC)	48
Maximum power (kWe)	3.9

CONTROLLER AND COMMUNICATION

Engine and light controller	SmartGen ALC708
Functions	Clock, auto start/stop, timer

TRAILER

Axle	Single
Stabilisers	4 x hydraulic
Suspension	Heavy duty 9 leaf steel
Brakes	Cable operated disc brakes with mechanical override
Wheels	Tyre and rim size 205 R16
Tow connection	2t, 50mm tow ball with 4 x Hamlok and 2 x Hooks
Electrical connection	Flat 7 pin connector
Max recommended tow speed (km/h)	80
Wind load rating as per AS1170 (km/h)	100

DIMENSIONS AND WEIGHTS (MAXIMUM)

Transport HxWxL (m)	2.49 x 2.08 x 4.71
Wet weight (t)	1.87
Number of units on 40ft trailer	3

INCLUSIONS

Safe two hand operation	Exhaust blanket
Single pole starter motor isolator (yellow)	2 x wheel chocks
Anderson jump start receptacle	Strap load binder
Emergency stop button	9kg fire extinguisher
Mudguards	Traffolyte pinned labels
Battery box	Rotating beacon for towing/fault alert
Fuel water separator	100mm black label
Wiggins oil evacuation	
2-pole Bosch battery isolator with locksafe actuator (red)	
Hydraulic lock - block the raise of the legs when mast is up	

STANDARD OPTIONS

Additional two 450W lights, increasing total light output to 513,000 lumens while maintaining a fuel consumption rate of 1.07 litres per hour.

Remote Services – Mactrack G70 with web and APP integration. NEXTG GPS location, ON/OFF status (subscription & SIM card required - not included)

Shackle tow connection 2 x additional wheel chocks

Round 7 pin trailer connector 75mm tow ring

Filter kit

CUSTOM OPTIONS

Allight has nearly 40 years of experience in customising lighting towers to customer specifications. Contact your sales representative for any of the options below or for your specific project needs.

Upgrade to 8 lights (684K lm total output) 1,000 hour service interval upgrade

Dual axles or skid based Hydraulic brakes on trailer

Customised componentry Custom colour finish

Wiggins hydraulic evacuation points

